## REACH FOR 140-P AND 140PXL SNOOPERS

SIDEWALK REACH 10' +/- a couple inches depending on truck frame.

<u> </u>		(what Miles is using at the moment)			
Parameter	140-P standard	140-P w/ 7 x 8'	140PXL	Comments	
	Platform	Platform	Platform		
Operating surface	5% grade 8% super elevation	5% grade 8% super elevation	2% grade 2% super elevation		
Number of rotation points	1	1	1		
·					
live load capacity	600 lbs	1,000 lbs	2,900 total*	*2,000 lbs payload, 900 personnel and tools	
. ,				, , , ,	
Platform size	24" wide x 13'-6" long	7' x 8'	4'X15' extending across		
	(27' long with bolt on extension)		the end of boom 3		+
		1			
	1	1			1
Boom 1 reach	16' long	16' long	21' long		+
			30.00		+
Boom 2 reach	Telescoping 16' to 28'	Telescoping 16' to 28'	Telescoping 21' to 29'		+
Doon's reach	Telescoping 11 11 11	relescoping 11 to 12	rerescoping == 15 =5		+
Boom 3 reach	n/a	n/a	telescoping 17' to 26'		+
Soon o reach	.,, -	192	telescoping 1. 15 15		+
Max underbridge reach obtainable	40'	21'	34'		+
Ivida dilacibilage reacti estamaste	40		3		+
1/22/2019				Aptus compare	
1/22/2013				Aptus compare	